"The Professional's Choice"



SUBMITTAL SHEET

Submittal Sheet #GSCSF

Grabber Acoustical Sound Sealant

Product:	ltem#	Description	Unit Pack		
	GSCSF	Grabber Acoustical Sound Sealant	12 tubes per case		
Product	Exceeds the requirements of ASTM C834. Tested in accordance with ASTM E84, ASTM E90 and ASTM C919.				
Features:	Meets NFPA	Class A fi re rating.			
	• Environmentally safe – VOC-compliant				
	 Eliminates sound transmission and seals air gaps Improves STC Values and upgrades sound quality 				
	LEED EQ Credit 4.1: Low-Emitting-material, Adhesives and Sealants				
	SCAQMD Rule 1168 Compliant				
	• UL 723 classified • Meets GS-36 requirements				
	Repairs cracks and eliminates rattles in drywall and plaster				
	Mold and mildew resistant				
	Easily tools with one pass				
	Cleans easily with water in wet state				
	Post-consumer recycled cartridge and carton				
	Paintable				

Sound	Edge Detail	STC Rating	Comments	
Transmission	Uncaulked	29	The open-edge track gave the STC value of 29 through direct leakage	
Class (STC) Ratings:	Single bead at the perimeter of one base layer	49	This bead closed void but did seal leakage around the joint between wallboard and track	
itatiliys.	Two beads, one under each base layer of gypsum board	53	The beads closed void and sealed leakage around track	

Note: Taken from ASTM C919. The test partitions of metal studs 610 mm (24 in.) on center, with double layers of 13 mm (0.5 in.)

Surface Burning	FLAME	SMOKE	Comments
Characteristics	0.0	0.0	Flame Smoke Tested as applied in two 1/4" diameter beads, 8 in. O.C.
For Building	0.0	0.0	(Coverage: 2.8 percent of the exposed test sample
materials:			area).



"The Professional's Choice"



Submittal Sheet #GSCSF

Submittal Approvals:				
Job Name				
Contractor	Date			
TRADEMARKS:	Notice:			
The following trademark used herein is owned by Grabber	We shall not be liable for incidental and consequential			
Construction Products, Inc.: GRABBER.	damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with			
	current printed instruction or for other than the intended use.			

Our liability is expressly limited to replacement of defective goods. Any claim shall be (30) days of the date it was or

reasonably should have been discovered.