

Acrylitex® Hand Texture

Acrylitex Hand Texture is an acrylic coating designed for use on interior walls and ceilings. It creates a durable, flame and mildew resistant finished surface for a variety of hand textures. It replaces traditional mud products and plasters.



Light, Medium and Heavy Textures

Single or Multi-tone



CREATES A FINISHED WALL SURFACE

Coverage

Hand Texture coverage will vary according to type of texture desired. Coverage can range from 125-200 square feet per gallon. Base coat – 185-200 square feet per gal. See Product Data Sheet.

Packaging

Available in 5 gallon containers.

Tinting

Product requires addition of colorant by distributor. Product may be tinted during manufacture with a minimum order of two pallets.

Preparation for Substrates of Gypsum, Plaster and Concrete

New gypsum or concrete surfaces must be clean, dry, structurally sound and properly cured. Joint compound must be thoroughly dry and sanded smooth. Remove all sanding and construction dust. Completely mask all other surfaces that will not be texture with product.

Application Equipment

Apply Acrylitex Base coat with a commercial grade airless sprayer or paint roller. Apply Acrylitex Hand Texture with hawk and trowel or pan and knife. Respirator not required but recommended for spray application. Clean tools, equipment and skin with soapy water and rinse. See Acrylitex Equipment tips.

Application

Acrylitex products may be applied by skilled tradesmen in the paint and/or texture fields. Product is bucket ready. No thinning necessary. Use at temperatures above 50° F. See Acrylitex Applicator Tips and/or call Technical Support at 541.617.9494 for additional information.