



Glue it, Screw it, & Seal it with Grabber

GSCSF - Professional Strength Acoustical Sound & Smoke Sealant

Non-flammable, water-based product developed specifically for the reduction of sound and smoke transmission in all types of wall partition systems. Easy application and easy cleanup. Used correctly and as directed, sealant will achieve and maintain specific STC (Sound Transmission Class) values specified for various wall system designs. This product should be used in office buildings, sound studios, hospitals, schools, hotels and motels, apartment complexes, and other areas where sound smoke ratings are required. This sealant is also ideal for sealing out air infiltration and unwanted moisture in residential construction.

- Improves STC Values and upgrades sound quality
- UL 723 classified
- Exceeds ASTM C834
- Test in accordance with ASTM E84, ASTM E90 and ASTM C919
- Meets NFPA Class A fire rating
- Smoke sealant



GSCSF - Green Products LEED Information

Surface Burning	Flame	Smoke	Tested as applied in two 1/4" diameter beads, 8 in. O.C. (Coverage: 2.8 percent of the exposed test sample area).
Characteristics For Building materials	0.0 0.0	0.0 0.0	

Product Features

Exceeds the requirements of ASTM C834. Tested in accordance with ASTM E84, ASTM E90 and ASTM C919. Meets NFPA Class A fire rating.

- Environmentally safe VOC-compliant
- Eliminates sound transmission and seals air gaps
- Improves STC Values and upgrades sound quality
- UL 723 classified
- Repairs cracks and eliminates rattles in drywall and plaster
- Mold and mildew resistant
- Easily tools with one pass
- Cleans easily with water in wet state
- Post-consumer recycled cartridge and carton

- LEED EQ Credit 4.1: Low-Emitting-material, Adhesives and Sealants.
- SCAQMD Rule 1168 Compliant
- Meets GS-36 requirements

All tubes are 28 oz. (828 ml) cartridges, 12 per case





Glue it, Screw it, & Seal it with Grabber

GDWAF - Professional Strength Drywall Adhesive

High quality, non-staining waterproof adhesive developed for adhering drywall to structurally sound surfaces. Primarily designed for bonding gypsum board to wood or metal studs, laminating gypsum board to gypsum board, and bonding gypsum board to concrete or block walls. When applied as directed, this adhesive combined with the approved mechanical fastener is the preferred method for permanent, safe installations without weak points. Product is widely used in new construction of single-family and multi-family homes, manufactured housing, commercial construction, and all remodeling, remedial and renovation projects where gypsum products are installed.

- Ideal for us on plywood, hardboard, gypsum wallboard, cold-rolled steel, galvanized steel and aluminum
- Exceeds the ASTM C-557 specification
- Strong initial tack allows panels to be positioned quickly without slipping
- Resists aging will not become hard or brittle
- Exposure to moisture or intermittent cold water immersion has little effect on the dried bond
- Fills irregularities and gaps in substrates, providing a more solid backup surface

GSFAF - Professional Strength Sub-floor Adhesive

Premium grade construction adhesive developed for Glued Floor Systems. Product is designed for interior or exterior use and forms a permanent waterproof and weatherproof bond to dry, wet, frozen lumber, either treated or untreated with high sheer strength. Adhesive is easy to use both on the job or on the production line. Ideal for use in most building projects that require adhesives.

- Works extremely well in colder temperatures
- Exceeds the performance requirements of the American Plywood Association AFG-01 Specification and ASTM C557
- Ideal for plywood, particleboard, OSB, and wet, frozen and ACA & CCA treated lumber
- Fills gaps and irregularities between materials to provide a more solid backup surface

All tubes are 28 oz. (828 ml) cartridges, 12 per case