# Aerosmith Fastening Systems



# **ST4200**

#### **Features**

- Lightweight only 4.8 lbs
- Depth of Drive Adjustment
- 360° adjustable exhaust deflector
- Uses Aerosmith brand flat wire welded fasteners
- Anti-Double fire mechanism
- Trigger Lock to prevent accidental firing
- Anti-Skid pad
- Shock absorbing comfort rubber handle
- Belt Clip
- Comes with plastic carrying case

## **Applications**

- Plywood to Steel 14 18 ga (68-43 mil)
- Exterior Gypsum to Steel 14 18 ga (68-43 mil)
- Cement Fiber Board to Steel 14 18 ga (68-43 mil)
- Steel to Steel 14 18 ga (68-43 mil)
- Stucco Lath Applications 14 18 ga (68 43 mil)

### **Specifications**

Height 11-1/4"" (285 mm) Width 4-2/5" (112.2 mm) Length 9-1/2" (241.5 mm) Weight 4.8 lbs (2.2 kgs)

Recommended Operating Pressure

**Loading Capacity** 

#### **Fastener Specifications**

Wire Welded Coil Fasteners

Shank Diameter

**Head Diameter** 

Recommended Fasteners

Accessories

70-120 psi (4.9-8.3 bar)

Up to 200 fasteners

3/4" - 1-1/2" (19-38 mm)

.100" (2.54 mm)

.197" - .312" (5.0 – 6.4 mm)

Aerosmith Helical, Gripshank Magnetic washer adapter UNM4100A Distributed by:



www.grabberman.com