

Submittal Sheet

Submittal Sheet #0309046-AD

Application:	Designed and engineered to work with all types of composite materials where surface mounted fasteners are recommended.
---------------------	--

Description:	The first screws designed and engineered to work with all types of composite materials where surface mounted fasteners are recommended. Patented LOX drive system delivers the maximum torque and guarantees fully driven screws...no cam outs or stripped recesses. Undercut head design leaves crisp clean finish...no mushrooms, no burrs. Reverse buttress fine thread design gathers loose materials and pulls it down and out of sight. Available in GrabberGard and Stainless Steel finishes for use in the harshest climates. Coarse threads and extra sharp points provide great holding power and fast starts. If you use power tools, you should use screws designed for power tools.
---------------------	--

Directions:	<p>Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and RPM range of 0 to 4,000.</p> <ul style="list-style-type: none">• The Flat head is fully seated when the head is flush with the work surface.• Overdriving may result in failure of the fastener or strip out of the work surface.
--------------------	--

Certifications:	All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASME B18.6.1, as referenced in ICC ER report ER-5280, are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.
------------------------	---

SUBMITTAL APPROVALS:

JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

PRODUCT SPECIFICATIONS	
Fastener Classification	Exterior Wood, Stainless Steel
Fastener Head	Undercut
Fastener Drive	LOX #2
Fastener Gauge	#9, #10
Fastener Point	QuickGrab
Fastener Package Type	Packaged Screws, Collated Screws (for automated feed systems)
Fastener Package Weight	5lb Box, Bulk Box
Fastener TPI	14, 15
Fastener Coating	316 Stainless Steel, GrabberGard
Fastener Color	Gray, Red, Brown