

POLY-CLASSIC® DGL Dura GlassTM Columns

- **EASY TO CUT AND INSTALL**
- **DECAY RESISTANT**
- LOW MAINTENANCE
- LIGHTWEIGHT COLUMNS

- **NOW AVAILABLE IN 30" ROUND**
- **IMPACT RESISTANT**
- LIMITED LIFETIME WARRANTY
- READY TO PRIME AND PAINT


| 22 800-423-3311


LIGHTWEIGHT FIBERGLASS COLUMNS EASILY HANDLE THE LOAD

Sometimes the most beautiful solutions are the most simple. Poly-Classic® DuraGlass™ square columns from Turncraft offer the classic beauty that homeowners and commercial property owners appreciate. Made from lightweight fiberglass, these columns are easy to cut, easy to install, and strong enough to carry heavy loads. Like other Poly-Classic® columns, DuraGlass™ columns are decay resistant and require little maintenance.

PLAN TYPES

Poly-Classic® Duraglass™ Columns are available in the following plan types. Please specify when you order. (Fractional components shown are typical. Customer may specify actual returns, wall thicknesses, etc.)









DURAGLASS™ NON-TAPERED SQUARE COLUMNS

		Shaft b	ottom †	Shat	t top	Space a	vailable shaft	
Column nominal	Shaft height	Outside width	Inside width	Shaft neck ‡	Astragal ring	For round	For square	Load
width †	(A)	(B)	(C)	(E)	(D)	support	support	capacity
8"	6' 8' 9' 10' 12'	7 5%"	7 1⁄8"	4 ½"	3/4"	6 ¾"	6 ¾"	5,000lb.
10"	6' 8' 9' 10' 12'	9 5%"	9 1⁄8"	5"	3/4"	8 ¾"	8 ¾"	6,000lb.
12"	6' 8' 9' 10' 12'	11 %"	11 ½"	5 ½"	3/4"	10 ¾"	10 ¾"	7,000lb.
16"	8' 10' 12' 14' 16' 18' 20'	15 %"	15 1⁄8"	7 %"	1"	14 ¾"	14 ¾"	20,000lb.




[†] Actual shaft net widths may vary from nominal size shown. ‡ Necking is shipped loose for pultruded columns. Spacing shown is typical, but may be adjusted by the installer. (Necking on 16" columns is integrated with the shaft.)



Tuscan Co	ap ar	nd B	ase
-----------	-------	------	-----

			Tuscan I	Base																				
Column	Plii	nth	Torus		Torus		Torus		Torus		Torus		Torus		Torus		Torus		Total height	Echinus	Aba	icus	Total height	
width	(A)	(B)	(C)	(D)	(B-D)	(E)	(F)	(G)	(E-F)	Material														
8"	10 %16"	1 ¾"	1 5/8"	1/2"	3 %"	1 ½16"	1 ¾"	10 11/16"	2 11/16"	ABS														
10"	12 19/16"	1 3/4"	1 1/8"	1/2"	3 %"	1 5⁄16"	1 ¾"	12 11/16"	2 11/16"	Pultruded FG														
12"	17"	2 ¾"	2 %"	7/8"	6"	1 1/8"	2"	17 1/4"	3 %"	Polyurethane														
16"	22 1/4"	3 %"	3 ¾"	1 1/8"	8 %"	2 13/16"	2 3/4"	22 ½"	5 %16"	Fiberglass														


DURAGLASS™ TAPERED BUNGALOW COLUMNS



Shaft	Shaft Specifications								
nominal bottom	Shaft bottom width NET	Shaft bottom inside width	Shaft top width NET	Shaft top inside width					
width *	(A)	(B)	(C)	(D)					
10"	9 5/8"	9"	5 5/8"	5"					
12"	11 5/8"	11"	7 5/8"	7"					
16"	15 5/8"	15	11 5/8"	11"					


^{*} Actual width is 3/8 less than nominal

Shaft		PVC	Base		PVC Cap					
nominal	Plinth width	Plinth height	Profile height	Total height	Abacus width	Abacus height	Profile height	Total height		
width	А	В	С	В-С	F	Е	D	D-E		
10"	13 5/8"	1"	1 1/4"	2 1/4"	9 5/8"	1"	1 1/8"	2 1/8"		
12"	15 5/8"	1"	1 1/4"	2 1/4"	11 5/8"	1"	1 1/8"	2 1/8"		
16"	19 5/8"	1"	1 1/4"	2 1/4"	15 5/8"	1"	1 1/8"	2 1/8"		



Ε

PVC Cap and Base




Shaft		Tuscar	n Base		Tuscan Cap				
nominal	Plinth width	Plinth height	Profile height	Total height	Abacus width	Abacus height	Profile height	Total height	
width	А	В	С	В-С	F	E	D	D-E	
10"	13 1/8"	1 11/16"	2"	3 11/16""	8 1/2"	1 7/16"	1 3/8"	2 13/16"	
12"	15 1/8"	1 11/16""	2"	3 11/16""	10 1/2"	1 7/16"	1 3/8"	2 13/16"	
16"	19 1/8"	1 11/16""	2"	3 11/16""	14 1/2"	1 7/16"	1 3/8"	2 13/16"	

DURAGLASS™ ROUND TAPERED COLUMNS

Standard DuraGlass™ column shafts are the same height as the listed size. Tuscan cap and base and Attic base go around the shaft, and do not affect the overall height. Ornamental capitals are set on top of the column astragal, and will affect the overall height: see the Poly-Classic® Ornamental Capitals specifications (page 18) for available capital sizes and more information.


		Shaft	neck	Shaft b	oottom *	Shaft	top *		available e shaft	
Column nominal	Shaft height	Neck height	Astragal ring	Outside diameter	Inside diameter	Outside diameter	Inside diameter	For round	For square	Load
diameter *	(A)	(B)	(C)	(D)	(E)	(F)	(G)	support	support	capacity
	8'									
	10'									
	12'									
	14'									
	16'									
30"	18'	13 %"	2 ½"	30"	29"	24 ½"	23 ½"	23"	16 ¼"	25,000 lb.
30	20'	15 /8	2 /2	30	23	2 7 7 2	25 /2	25	10 /4	25,000 lb.
	22'									
	24'									
	26'									
	28'									
	30'									

^{*} Actual shaft net diameters may be smaller than nominal size shown.



Column	olumn Plinth		То	Torus		Echinus	Abacus		Total height	
diameter	(A)	(B)	(C)	(D)	(B-D)	(E)	(F)	(G)	(E-F)	Material
30"	40 ½"	7 1/4"	6 ½"	2 ¾"	16 ½"	4 1/16"	5 1/8"	35 ¾"	9 %16"	Fiberglass

		Optional Attic Base									
Column	Plii	Plinth Torus Total height									
diameter	(A)	(B)	(C)	(C) (D) (E) (F)				Material			
30"	40 ½"	7 1/4"	3 %"	3 %"	2 %"	1 %"	19 1/4"	Fiberglass			



Attic Base


DURAGLASS™ ROUND NON-TAPERED COLUMNS

Standard DuraGlass™ column shafts are the same height as the listed size. Tuscan caps and bases and Attic bases go around the shaft, and do not affect the overall height. Tuscan bases are used (upside-down) as caps. Ornamental capitals are not available for non-tapered shafts.

Tuscan Cap

		Shaft bottom *		Shaft	top *	Space a		
Column nominal	Shaft height	Outside diameter	diameter diameter diam		Inside diameter	For round	For square	Load
diameter *	(A)	(B)	(C)	(B)	(C)	support	support	capacity
	8'							
	10'							
30"	12'	30"	29"	30"	29"	28 ½"	20 1/8"	25,000 lb.
	14'							
	15'							

^{*} Actual shaft net diameters may be smaller than nominal size shown.



		Tus	can Ba	ise			Τι	ıscan	Сар		
Column	Plinth		Torus		Total height	Echinus		Abacus		Total height	
diameter	(A)	(B)	(C)	(D)	(B-D)	(D)	(C)	(B)	(A)	(B-D)	Material
30"	40 ½"	7 1/4"	6 ½"	2 ¾"	16 ½"	2 ¾"	6 ½"	7 1/4"	40 ½"	16 ½"	Fiberglass

Tuscan Cap and Base