

Hang Tite Fast Tacking Construction Adhesive

There's just no way around it. . . you still get what you pay for.

- ▶ **High performance**
- ▶ **Low soak in**
- ▶ **Uniform mist spray**

Purchase by the case and save!

Properties	Per Can	Grabber Hangtite	3M 77	COMPARE
180° Peel Strength (PLI)		6.25	2.90	2-1/2 times greater bond strength.
Shear Strength (PSI)		63.1	6.10	10 times greater shear strength for strong bonds, and less failure.
Green Shear Strength (PSI)	5Min	1.3	1.3	Both products develop bond strength rapidly for less chance of bond failure.
Does NOT Contain CFC's		Yes	Yes	Contains no ozone depleting chemicals.
Uniform Mist Spray		Yes	No	Delivers a more uniform spray pattern.
Color		Water White	Light Amber	Minimizes effects of over-spray.
Max Temperature Resistance Min @ 160° F		183° 9°	163° 4°	Higher temperature capability reduces adhesive failure.
Remains Pressure Sensitive		Yes	Yes	Long open time minimizes application errors.
Temporary or Permanent Bonds		Yes	Yes	Versatile.

If it's worth building. . .it's worth *GRABBER*.

Visit your local Grabber dealer to learn more or visit grabberman.com to find a dealer near you.