


**Cement Board****Product #290****GRABBER® USG® Structural Panel fastener** (1 OF 2)**Designed for USG Structural Panels.****Finish - GRABBERGARD****Wafer  
Head****Drill Point****LOX #2****APPLICATIONS**

- ▶ For attachment of sheathing, siding, OSB or plywood to steel.

**PRODUCT FEATURES**

- ▶ The USG Structural Panel screw has "reamer nibs" under the head to ease countersinking and leave smooth clean edges.
- ▶ Wings allow the screw to drill into the metal without clogging the threads and racking/lifting the material before it penetrates through the metal.

**SPECIFICATIONS**

- ▶ Gauge - #8
- ▶ Length — 1-1/4" to 2-3/8"
- ▶ Head Type — Thin Wafer
- ▶ Recess Type — LOX® #2
- ▶ Thread Type — Single Lead
- ▶ Finish — GRABBERGARD
- ▶ Head diameter - .362 inch
- ▶ GRABBER screws are manufactured in an ISO 9002 and ISO 14001 certified and approved factory, and are approved by ICC ESR report ESR-1271.

**INSTALLATION GUIDELINES**

- ▶ Use a standard screwgun with a depth-sensitive nose piece. Suggested screwgun specification for optimal performance — 4 amps minimum and RPM range of 0 to 4,000.
- ▶ Proper depth setting is paramount in this application.
- ▶ Overdriving may result in failure of the fastener or stripout of the work surface.
- ▶ The fastener must penetrate beyond the metal a minimum of three thread pitches.

**Cement Board**
**Product #290**
**GRABBER® USG® Structural Panel fastener** (2 OF 2)

**PRODUCT SIZES AND ORDERING INFORMATION**

Catalog No.	Gauge/Length	Length Metric	Quantity Per Carton	Weight Per Carton
CGH8114LG	#8x1-1/4"	32 mm	1 M	
CGH8158LG	#8x1-5/8"	41 mm	1 M	
CGH8238LG	#8x2-3/8"	63 mm	1 M	
GH8114LG	#8x1-1/4"	32 mm	5 M	32.00(lbs)
GH8158LG	#8x1-5/8"	41 mm	4 M	30.00(lbs)
GH8238LG	#8x2-3/8"	63 mm	3 M	30.00(lbs)

\*Collated screw packaging option available on selected items.

**PRODUCT DIMENSIONS (MILLIMETERS)**

Gauge	B Head Dia	Recess Depth	W Gauging Width	d Shank Dia	d1 Minor Dia	d2 Major Dia	TPI
#8	7.77	1.80	#2	3.28	2.85	4.05	18
	8.18	2.46		3.32	3.05	4.25	


**STANDARD CORROSION TEST RESULTS**

Finish	Test	Standard/Protocol	Results
GRABBERGARD	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GRABBERGARD	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust

**Pull-out and Shear Test Data\*\***

Screw Gauge	Metal Gauge	Tension (lbs.)	Shear (lbs.)
#8	14	450	1012
	16	442	955
	18	340	1045

\*\*GRABBER fasteners are not categorized as structural bolts. The figures listed above are ultimate average values achieved under independent laboratory conditions, and apply to GRABBER Line fasteners only. An appropriate safety factor must be determined by a qualified professional for design purposes.


**DRILLING CAPACITY**

Screw Gauge	Drill Point	Max Panel Thickness	Steel Thickness Gauge Range
8	3	0.100-0.140	20-12

All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C1513, as referenced in ICC ESR report ESR-1271, are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.

