



#1 CHOICE OF PROFESSIONALS®

HE102 – AQUA-PRIME

Physical Properties

-Appearance.....Water like liquid	-Flash Point.....>212°F
-Application Temperature.....45° to 104°F	-Maximum VOC.....90 g/l
-Color.....Aqua	-Service Temperature (cured bead).....-40° to 158°F
-Drying Time @ 50% R.H. 68°F (20°F)	-Solids by Volume.....37%
Initial Set.....30 min.	-Solids by Weight.....35.2%
Through set.....2 hrs.	-Specific Gravity @ 77°F (25°C).....1.02
-Flammability	-Weight per Gallon.....8.2 – 8.7 lbs.
WetNon-Flammable	
Dry.....Burns	

Packaging

Gallon (9.59 lb.)	5 Gallon (33 lb.)
-------------------	-------------------

Description

HE102 - AQUA-PRIME is a polymer emulsion based primer for self-adhesive membranes.

Features

Features:

- Quick Drying
- Tacky film provides positive adhesion of membrane
- Easily applied by spray, brush or roller
- Environmentally friendly - low VOC content
- Non-flammable during application
- Water based, no solvent odors

Uses

HE102 – AQUA-PRIME is used as a primer for self-adhered membranes such as *modified PLUS™ SA*, **Blueskin®SA**, **Blueskin® PE 200 HT**, **Blueskin® WP200** and **Low Slope** when applied to masonry, concrete, wood and gypsum board. **HE102** is the product of choice when it is necessary to achieve a fast drying, solvent free, tacky surface that can be walked on without pickup. This is important for the application of membranes on horizontal surfaces.

Surface Preparation

Surfaces must be dry and free from dust, dirt, grease, oil, or other foreign matter.

Application

Apply by garden sprayer, airless, air assisted, or air spray equipment. Pour primer from container into sprayer and spray fine mist over entire substrate. Primer may also be applied by brush or by roller. Allow primer to dry to a tacky film before applying membrane. Primer surfaces not covered by membrane during the same working day must be reprimed. **HE102 – AQUA-PRIME** is intended to be used as supplied and should not be diluted.

HE102 – Aqua-Prime

Coverage

Up to 500 sq. ft./gal. depending on porosity and texture of the surface.

Precautions

Protect from freezing during shipping and application. Store product above 32°F. If frozen, allow to thaw at room temperature and mix prior to use.

Cleanup

For uncured film, use water. Use mineral spirits for cured films.

Caution

Do not take internally. Harmful if swallowed. If swallowed, CALL PHYSICIAN IMMEDIATELY! Avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. GET MEDICAL ATTENTION! **In case of accidental injection** by power spray equipment, GET MEDICAL ATTENTION IMMEDIATELY! Repeated or prolonged contact with skin can cause irritation. Will cause eye irritation if not washed immediately. If applied by spray, mist or vapor can cause problems if inhaled. Use safety goggles if applied by spray. Keep container closed when not in use. Dispose of container and unused contents in accordance with Local, State, and Federal regulations.

Dispose of container and unused contents in accordance with Local, State, and Federal regulations.

FOR EXTERIOR USE ONLY.

KEEP OUT OF REACH OF CHILDREN.

KEEP FROM FREEZING.

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, birth defects, and other reproductive harm.

For more information, visit www.henry.com or for technical assistance call us at 800-486-1278. For more information on Henry's® product warranty and liability disclaimer please visit www.henry.com/warranty. Refer to the Safety Data Sheet prior to using this product. The Safety Data Sheet is available at www.henry.com or by emailing Henry® Product Support at productsupport@henry.com or by calling 800-486-1278.

® Henry and Blueskin are registered trademarks of Henry Company

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry® Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.