

PRODUCT SPECIFICATIONS

C-SERIES UNDEREAVE VENT

1.1 MATERIALS:

1.1.1 Aluminum Alloys: Conform to ASTM B209.

0.019" Aluminum Coiled Sheet.

Screen: 10 mil, 8x8 mesh Aluminum Screen.

1.1.2 Paint: Factory applied baked on Valspar Super Flex with minimum 0.8 top coat and minimum 0.3 wash coat.

1.3 MISCELLANEOUS:

1.3.1 Description: Under eave mounted attic intake vent. Louvers are stamped and formed, and the screen is securely held in place. This is an intake vent and must be used in conjunction with adequate exhaust vents for proper operation.

1.3.2 Color: Available in BROWN, WHITE, and MILL finish.

1.3.3 Net Free Area: 25-65 square inches per unit.

1.3.4 Dimensions:

C416: Overall: 16" x 4", NFA: 25 in².

C616: Overall: 16" x 6", NFA: 37 in².

C816: Overall: 16" x 8", NFA: 65 in².

1.2.5 Packaging: Packaged 12 units per inner carton, 6 inner cartons per master carton (72 total units). UPC labels are affixed to each vent and carton.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax