

PRODUCT SPECIFICATIONS

DRB-24 CUPOLA

1.1 MATERIALS:

1.1.1 Aluminum Alloys: Conform to ASTM B209 and ASTM B221.

Top Cap: 0.065" Aluminum Coiled Sheet.

Top: 0.032" Aluminum Coiled Sheet.

Sides: 0.032" Aluminum Coiled Sheet.

Side Support: 0.032" Aluminum Coiled Sheet.

Rain Shield: 0.0175" Aluminum Coiled Sheet.

Side Brace: .032" Aluminum Coiled Sheet.

Base Bracket: .032" Aluminum Coiled Sheet.

Adj. Base Left: 0.032" Aluminum Coiled Sheet.

Adj. Base Right: 0.032" Aluminum Coiled Sheet.

Corner Bracket: 0.058 Aluminum Coiled Sheet

Top Clip: 0.058 Aluminum Coiled Sheet

1.1.2 Screen: 18x18 mesh Aluminum Screen.

1.1.3 Paint: Factory applied baked on Valspar Super Flex with minimum 0.8 top coat and minimum 0.3 wash coat.

1.2 MISCELLANEOUS:

1.2.1 Description: Cupola style, self-flashing roof mounted attic exhaust vent. Adjustable to roof pitches from 2/12 to 6/12. Features a bird-proof construction, with all connections securely riveted. Internal rain shield and bug screen keeps weather infiltration and insects out of the attic. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color: Available in WHITE.

1.2.3 Dimensions: Overall – 24" x 24" x 24", Hole Size – 17x17"

1.2.4 Packaging: Packaged one to a carton. UPC labels are affixed to each carton.

1.3 Additional Options:

1.3.1 Weather Vanes: Include an ornamental pole and directional. Weather vanes are cast aluminum with a black enamel finish. Four styles are available.



P.O. Box 519
Jacksonville, AR 72078
1-800-643-5596 phone
501-982-1258 fax