

Low profile ridge vent installs with hammer or nail gun.



9" Wide for  
Enhanced Ridge  
Cap Shingles.



**CLASS A FIRE RATING** **CLASS A FIRE RATING** **CLASS A FIRE RATING** **CLASS A FIRE RATING** **CLASS A FIRE RATING** **CLASS A FIRE RATING** **CLASS A FIRE RATING**

**CLASSIFIED**  
UL  
RIDGE VENTS - CLASS A AS TO EXTERNAL  
FIRE EXPOSURE WHEN INSTALLED IN  
ACCORDANCE WITH INSTRUCTIONS  
PROVIDED WITH RIDGE VENTS

Full UL mark included on vent.

Unique OmniRidge®  
perpendicular baffles  
enhance air flow.

Louvers positioned  
closer to wind stream  
for better air flow.

Molded-in  
endplug.

Aerodynamically  
curved internal baffles  
to minimize wind  
resistance.

Weatherproof under-lapping joint  
prohibits weather infiltration.

## LOR9-4FR FEATURES:

- ▶ Sonic welded fiberglass screen provides enhanced weather protection.
- ▶ Pneumatic nail gun or hammer installed.
- ▶ Four drain holes per foot per side.
- ▶ 11 square inches of net free area per linear foot.
- ▶ External venturi baffle.
- ▶ Nail holes marked every 6 inches - supported every foot.
- ▶ Preformed to 3/12 pitch.
- ▶ Molded nail lines.
- ▶ Molded centerline for fast and easy alignment.
- ▶ Alignment tabs.
- ▶ External water shield.
- ▶ Slot width guide lines.
- ▶ Patented molded-in fanfolded endplug fits all roof pitches.
- ▶ **Lifetime Limited Warranty.**

Model	Length (ft.)	NFA (in. <sup>2</sup> )	Roof Pitch	Per Box
LOR9-4FR	4'	44	2/12 to 16/12	10

How many LOR9-4FR Vents do you need?

Attic floor space to be ventilated in square feet:

EXHAUST SYSTEMS	Attic floor space to be ventilated in square feet:																																																																							
	1000												1500												2000												2500												3000												3500											
	Intake												Intake												Intake												Intake												Intake												Intake											
	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9	Exhaust	C416	C616	C816	105/190	140	SV-10	DA-4/IV-9																								
	22'	10'	7'	4'	4'	3'	4'	7'	33'	15'	10'	6'	6'	5'	6'	11'	44'	20'	14'	8'	7'	6'	8'	14'	55'	25'	17'	10'	9'	7'	10'	17'	66'	30'	20'	12'	11'	9'	12'	21'	77'	34'	23'	14'	12'	10'	14'	24'																								
LOR9-4FR	22'	10'	7'	4'	4'	3'	4'	7'	33'	15'	10'	6'	6'	5'	6'	11'	44'	20'	14'	8'	7'	6'	8'	14'	55'	25'	17'	10'	9'	7'	10'	17'	66'	30'	20'	12'	11'	9'	12'	21'	77'	34'	23'	14'	12'	10'	14'	24'																								

MADE IN USA

LO450\_1218