

## OmniRidge<sup>®</sup> Pro

**Our NEWEST Advanced Feature Low Profile Vent!** 



## **PRO4-N FEATURES:**

- Advanced low profile design.
- Includes 2½" ring shank nails, 30 nails per piece.
- Internal baffles.
- External "Omni" baffles.
- External Venturi baffle.
- ▶ "Posi-tabs" contour to shingles for improved weather protection.
- Weatherproof underlapping joints.
- ▶ 6 drain holes per side per foot.
- ▶ 18 square inches of Net Free Area per linear foot.
- 10 supported nail holes
- ▶ Preformed to 2/12 pitch.

- Fits roof pitches 2/12 to 16/12.
- Molded-in shingle nail lines, reinforced every 2 inches.
- Slot width guide lines.
- Continuous molded end plug for improved weather protection.
- Lifetime Limited Warranty.







Want more info? Scan the QR code to access additional information on lomanco.com.

Model	Length (ft.)	NFA (in. <sup>2</sup> )	Roof Pitch	Packaged	
PRO4-N	4'	72	2/12 To 16/12	10 Per Box	

## **PR04-N Ventilation Guide**

(Attic floor space) in square feet

Area Ventilated	1000	1500	2000	2500	3000	3500
PRO4-N Required (ft.)	14'	20'	27'	34'	40'	47'
Intake Required (in <sup>2</sup> )	252	360	486	612	720	846

Based on the IRC/FHA standard of one square foot of ventilation for every 300 square feet of attic floor space.

lomanco



MADE IN USA LO453\_0419