



The Shingle Over Ridge Vent with Proven Performance!

OR4-S FEATURES:

- ▶ Sonic welded fiberglass screen provides enhanced weather protection.
- ▶ Internal aerodynamic curved baffles.
- ▶ External perpendicular omni baffles.
- ▶ Weatherproof underlapping joint.
- ▶ Four drain holes per foot per side.
- ▶ 18 square inches of Net Free Area per linear foot.
- ▶ External venturi baffle.
- ▶ Pre-formed to 3/12 pitch.
- ▶ 10 supported nail holes.
- ▶ Molded nail lines.
- ▶ Alignment tabs.
- ▶ External water shield.
- ▶ Slot width guide lines.
- ▶ Molded-in fanfolded endplug.
- ▶ **Lifetime Limited Warranty.**



Want more info?
Scan this QR
code with your
smartphone.

OR4-S Ventilation Guide

(Attic floor space) in square feet

Area Ventilated	1000	1500	2000	2500	3000	3500
Number Required	4	5	7	9	10	12
Intake Required(in ²)	288	360	504	648	720	864

Based on the IRC/FHA standard of one square foot of ventilation for every 300 square feet of attic floor space.

Model	Length (ft.)	NFA (in. ²)	Roof Pitch	Packaged
OR4-S	4'	72	2/12 To 16/12	10 Per Box

CFM at Wind Velocity of		
3 MPH	8 MPH	15 MPH
95	235	430

Above CFM are per 4-Ft. Sections

LO441_0413

Find us on
Facebook

Follow us on
Twitter



1.800.643.5596 • Lomanco, Inc. • lomanco.com