

External Venturi and "Omni" baffles provide enhanced airflow.



Sonic welded fiberglass screen provides enhanced weather protection.

Unique "posi-tabs" contour to shingles for improved weather protection.

Continuous molded end plug and underlap prohibit weather infiltration.

Fully supported nail holes.

PRO4SWN FEATURES:

- ▶ Sonic welded fiberglass screen provides enhanced weather protection.
- ▶ Advanced low profile design.
- ▶ Includes 2½" ring shank nails, 30 nails per piece.
- ▶ Internal baffles.
- ▶ External "Omni" baffles.
- ▶ External Venturi baffle.
- ▶ "Posi-tabs" contour to shingles for improved weather protection.
- ▶ Weatherproof underlapping joints.
- ▶ 6 drain holes per side per foot.
- ▶ 18 square inches of Net Free Area per linear foot.
- ▶ 10 supported nail holes
- ▶ Preformed to 2/12 pitch.
- ▶ Fits roof pitches 2/12 to 16/12.
- ▶ Molded-in shingle nail lines, reinforced every 2 inches.
- ▶ Slot width guide lines.
- ▶ Continuous molded end plug for improved weather protection.
- ▶ **Lifetime Limited Warranty.**




Model	Length (ft.)	NFA (in. ²)	Roof Pitch	Packaged
PRO4SWN	4'	72	2/12 To 16/12	10 Per Box

PRO4SWN Ventilation Guide

(Attic floor space) in square feet

Area Ventilated	1000	1500	2000	2500	3000	3500
PRO4SWN Required (ft.)	14'	20'	27'	34'	40'	47'
Intake Required (in ²)	252	360	486	612	720	846

Based on the IRC/FHA standard of one square foot of ventilation for every 300 square feet of attic floor space.



Want more info?
Scan the QR code
to access additional
information on
lomanco.com.