




## The Rolled Vent That Works!

Use with Lomanco intake vents for a complete ROOF VENTILATION SYSTEM

### OR-20 FEATURES:

- ▶ Patented design brings you the truly functional roll out.
- ▶ Compact 20 foot roll is easy to handle.
- ▶ Superior weather protection and no filter to clog.
- ▶ Exterior convolute baffles incurved design allows the flexibility to roll up and out while maintaining shape.
- ▶ Can be cut at one foot intervals, multiple cut lines eliminate unnecessary scrap.
- ▶ Patented molded fanfold end plugs, no accessories or alterations needed.
- ▶ Field tested design - the air flow acceleration design - maximizes ventilation capacity.
- ▶ Omni baffles mean air flow from any direction.
- ▶ Supported nail holes, placed every foot, will not crush down.
- ▶ Full 18 square inches of Net Free Area per linear foot.
- ▶ Engineered material guarantees longevity.
- ▶ **Lifetime Limited Warranty.**



### OR-20 Ventilation Guide

(Attic floor space) in square feet

Area Ventilated	1000	1500	2000	2500	3000	3500
Required length(feet)	14	20	27	34	40	47
Intake Required(in <sup>2</sup> )	252	360	468	612	720	846

Based on the IRC/FHA standard of one square foot of ventilation for every 300 square feet of attic floor space.

Model	Length (ft.)	NFA (in. <sup>2</sup> )	Roof Pitch	CFM at Wind Velocity of		
				3 MPH	8 MPH	15 MPH
OR-20	20'	360	2/12 To 16/12	95	235	430

Above CFM are per 4-Ft. Sections



Want more info?  
Scan this QR  
code with your  
smartphone.

Find us on  
**Facebook**

Follow us on  
**Twitter**



1.800.643.5596 • Lomanco, Inc. • lomanco.com