

LomanCool™ 2000

- ▶ Deep drawn flange and unique rain shield keep water out.
- ▶ 8x8 aluminum screen attached for insect protection.
- ▶ Factory-set adjustable thermostat (switches on at 100 degrees and off at 85 degrees).
- ▶ Thermostat features a "push-to-test" button.
- ▶ 2000TH model is equipped with thermostat/humidistat combo switch.
- ▶ Adjustable humidistat settings are: minimum 80%, normal 42%, and maximum 20%.
- ▶ 5 Year Limited Warranty.

Colors Available:



How many Power Vents do you need?

Copper 2000/2000TH
Also available in copper.

POWER VENT EXHAUST SYSTEMS	Attic floor space to be ventilated in square feet:					
	1000	1500	2000	2500	3000	3500
2000/2000TH	1	2	2	3	3	4
1800*	1	2	2	3	3	4

*NOTE: Lomanco recommends the use of one gable vent per gable end of structure. Your roof must have the required number of gable ends to install the proper number of gable vents for a balanced ventilation system.

Add-A-Vent 1800

- ▶ Factory-set adjustable thermostat (switches on at 100 degrees and off at 85 degrees).
- ▶ Can be mounted in horizontal or vertical position on either 16" or 24" center framing members.
- ▶ Optional humidistat is adjustable to fit individual attic humidity levels.
- ▶ Designed to mount behind existing gable louver.
- ▶ 5 year limited warranty.



MIAMI-DADE COUNTY
APPROVED
LomanCool 2000

CSA
Approved
LomanCool 2000, 1800

Texas Department of
Insurance "Windstorm"
Approved
LomanCool 2000

UL
All Models



Want more info?
Scan this QR
code with your
smartphone.

Model	Amps	Motor		Volts	Base (in.)	Fan Blades	
		HP	RPM			No.	DIA. (in.)
2000	3.4	1/10	1100	120	20 x 23	5	12
2000TH	3.4	1/10	1100	120	20 x 23	5	12
1800	3.4	1/10	1100	120	—	5	12