# LOMANCO Tile Roof Whirlybird®




- Approved for all tile and slate roof constructions.
- Permanently lubricated upper and lower ball bearings that ensure long life and no maintenance.
- All-aluminum rust-free construction.
- Rigid spider-type structure.
- ▶ Riveted at every connection.
- 21 air-foil curved vanes with rolled edges to deflect water.

- Exclusive vari-pitch base adjusts up to 12/12 roof pitch.
- Large flashing for easy installation.
- Tested to withstand winds of 110 m.p.h.
- Forever Guarantee residential use only.
- **Easy installation.**

### **BEARING FACTS**

Molded and fully machined raceways - not merely molded. Concentric to .0015 for low drag and quiet operation.

DuPont Delrin® inner and outer bearing rings - the longest lasting and smoothest polymer ball bearing material available.



100 Grade 302 series stainless steel balls for low turning resistance and high resistance to moisture.

#### COLORS AVAILABLE

















MIAMI-DADE COUNTY

Lomanco, Inc.

Jacksonville, AR

## Hurricane caps available!

Model	Hole Size	Height	Base
B I B-12TR	12	201/4	20 x 20
BEB-12TR	12	20%	20 x 20



# How many Whirlybirds® do you need? Your attic floor space to be ventilated in square feet.

1000 1500 2000 2500 3000 3500

TURBIN	IE V	ENT	EXHA	UST	SYST	ЕМ
BIB-12TR	2	2	3	4	4	5
BEB-12TR	2	2	3	4	4	5
TURBIN	IE V	ENT	INTAI	KE SY	STE	N
C416	21	21	32	42	42	53
C616	15	15	22	29	29	36
C816	9	9	13	17	17	21
105/190	8	8	11	15	15	19
140	6	6	9	12	12	15
C) / 10	_	_	4.2	47	47	24

LO462-1111





