SAFETY DATA SHEET

CIA-GEL 7000 PART A



Section 1. Identification

GHS product identifier : CIA-GEL 7000 PART A

Other means of identification

:

Product type :

Relevant identified uses of the substance or mixture and uses advised against

Identified uses :

Supplier's details :

Emergency telephone number (with hours of operation)

. .

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 1C SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

TOXIC TO REPRODUCTION (Fertility) - Category 1B TOXIC TO REPRODUCTION (Unborn child) - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) -

Category 1

AQUATIC HAZARD (LONG-TERM) - Category 2

Carcinogenicity

: This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of this product will create a possible dust hazard).

This product contains crystalline silica (quarts sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of this product will create a possible silica dust hazard.)





Section 2. Hazards identification

GHS label elements

Hazard pictograms









Signal word

Danger

Hazard statements

: H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H350 - May cause cancer.

H360 - May damage fertility or the unborn child.

H372 - Causes damage to organs through prolonged or repeated exposure. (respiratory

tract)

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.

P273 - Avoid release to the environment.

P260 - Do not breathe dust.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash hands thoroughly after handling.

P272 (OSHA) - Contaminated work clothing must not be allowed out of the workplace.

Response

: P391 - Collect spillage.

P314 - Get medical attention if you feel unwell.

P308 + P313 - IF exposed or concerned: Get medical attention.

P304 + P310 - IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Immediately call a POISON CENTER or physician.

P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER

or physician. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing

before reuse. Immediately call a POISON CENTER or physician.

P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash

contaminated clothing before reuse.

P333 + P313 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage

: P405 - Store locked up.

Disposal

: P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Other means of identification



Section 3. Composition/information on ingredients

Ingredient name	%	CAS number	
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	≥75 - ≤90	25085-99-8	
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane	≥5 - ≤10	30499-70-8	
Crystalline silica, respirable powder	≥3 - ≤5	14808-60-7	
Titanium dioxide	≥1 - ≤3	13463-67-7	
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane Crystalline silica, respirable powder	≥5 - ≤10 ≥3 - ≤5	30499-70-8 14808-60-7	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness





Section 4. First aid measures

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide halogenated compounds

metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.



Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Use respirator only if ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.





Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis-, homopolymer	None.
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl) oxirane	None.
Crystalline silica, respirable powder	OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / (%SiO2+2) 8 hours. Form: Respirable NIOSH REL (United States, 10/2016). TWA: 0.05 mg/m³ 10 hours. Form: Respirable dust OSHA PEL (United States, 6/2016). TWA: 50 µg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 3/2017).
Titanium dioxide	TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction ACGIH TLV (United States, 3/2017). TWA: 10 mg/m³ 8 hours. OSHA PEL (United States, 6/2016). TWA: 15 mg/m³ 8 hours. Form: Total dust

Appropriate engineering controls

Environmental exposure controls

- : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.



Section 8. Exposure controls/personal protection

Respiratory protection

Based on the hazard and potential for exposure, if required, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Gel. Solid.
Color : White.
Odor : Mild.

Density : Not available. **Odor threshold** Not available. pН Not available. **Melting point** Not available. **Boiling point** Not available. Flash point : Not applicable. **Evaporation rate** : Not available. Flammability (solid, gas) : Not applicable. Lower and upper explosive : Not applicable.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.
Specific gravity : Not available.
Solubility : Not available.
Partition coefficient: n- : Not available.

Partition coefficient: n octanol/water

octanon/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not applicable.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Volatile organic compounds : See section 9 of part B for VOC content.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials: Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.





Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

There is no data available.

Irritation/Corrosion

There is no data available.

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
Crystalline silica, respirable powder Titanium dioxide	-	1 2B	Known to be a human carcinogen.

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

Name	Category	Target organs
Crystalline silica, respirable powder	Category 1	respiratory tract

Aspiration hazard

There is no data available.

Information on the likely

routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations





Section 11. Toxicological information

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

effects

: No known significant effects or critical hazards.

Potential delayed effects

: No known significant effects or critical hazards.

Long term exposure

Carcinogenicity

Potential immediate

effects

: No known significant effects or critical hazards.

: No known significant effects or critical hazards.

Potential chronic health effects

Potential delayed effects

General : Causes damage to organs through prolonged or repeated exposure. Once sensitized, a

severe allergic reaction may occur when subsequently exposed to very low levels. May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: May damage the unborn child.

Developmental effects: No known significant effects or critical hazards.

Fertility effects : May damage fertility.

Numerical measures of toxicity

Acute toxicity estimates

There is no data available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium dioxide	Acute LC50 >1000000 μg/L Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

There is no data available.

Bioaccumulative potential

There is no data available.





Section 12. Ecological information

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Should be mixed with Part B. The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	Not regulated.	UN3077	UN3077
UN proper shipping name	-	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Oxirane, 2,2'-[(1-methylethylidene)bis(4, 1-phenyleneoxymethylene)]bis-, homopolymer, 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane). Marine pollutant (Oxirane, 2,2'-[(1-methylethylidene)bis(4, 1-phenyleneoxymethylene)]bis-, homopolymer, 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Oxirane, 2,2'-[(1-methylethylidene)bis(4, 1-phenyleneoxymethylene)]bis-, homopolymer, 1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-(chloromethyl)oxirane)
Transport hazard class(es)	-	9	9
Packing group	-	III	III
Environmental hazards	No.	Yes.	Yes.

AERG : 171

Additional information

The limited quantity exception can be used for the transportation of this item. Certain restrictions may apply in regards to sizes and packaging. For further information, refer to the applicable transportation of dangerous goods regulation.

DOT Classification

- : This product is not regulated as a marine pollutant when transported on inland waterways in sizes of ≤5 L or ≤5 kg or by road, rail, or inland air in non-bulk sizes, provided the packagings meet the general provisions of §§ 173.24 and 173.24a.
- **IMDG**: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.





Section 14. Transport information

IATA

The environmentally hazardous substance mark may appear if required by other transportation regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) PAIR: Siloxanes and Silicones, di-Me, reaction products with silica United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals

: Not listed

(Essential Chemicals)

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : SKIN CORROSION/IRRITATION - Category 1C

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

TOXIC TO REPRODUCTION (Fertility) - Category 1B TOXIC TO REPRODUCTION (Unborn child) - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) -

Category 1

Composition/information on ingredients

Name	Classification
Oxirane, 2,2'-[(1-methylethylidene)bis(4,	SKIN CORROSION/IRRITATION - Category 2
1-phenyleneoxymethylene)]bis-, homopolymer	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	SKIN SENSITIZATION - Category 1
1,3-Propanediol, 2-ethyl-2-(hydroxymethyl)-, polymer with 2-	SKIN CORROSION/IRRITATION - Category 1C
(chloromethyl)oxirane	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
	SKIN SENSITIZATION - Category 1B
	TOXIC TO REPRODUCTION (Fertility) - Category 1B
	TOXIC TO REPRODUCTION (Unborn child) - Category 1B
Crystalline silica, respirable powder	CARCINOGENICITY - Category 1A
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory
	tract) (inhalation) - Category 1
Titanium dioxide	CARCINOGENICITY - Category 2



Section 15. Regulatory information

SARA 313

There is no data available.

State regulations

Massachusetts

: The following components are listed: Crystalline silica, respirable powder; Titanium

dioxide

New York

: None of the components are listed.

New Jersey

: The following components are listed: Crystalline silica, respirable powder; Titanium

Pennsylvania

The following components are listed: Crystalline silica, respirable powder; Titanium dioxide

California Prop. 65

♠ WARNING: This product can expose you to chemicals including Titanium dioxide, Crystalline silica, respirable powder, which are known to the State of California to cause cancer, and Ethanediol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

•	•	
Ingredient name	•	Maximum acceptable dosage level
Titanium dioxide Ethanediol Crystalline silica, respirable powder	- - -	Yes.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 1C	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION (Fertility) - Category 1B	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) -	Calculation method
Category 1	
AQUATIC HAZARD (LONG-TERM) - Category 2	Calculation method

History

: 08/28/2018 Date of issue mm/dd/yyyy Date of previous issue : Not applicable

Version : 1





Section 16. Other information

Prepared by

: KMK Regulatory Services Inc.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



SAFETY DATA SHEET

CIA-GEL 7000 PART B



Section 1. Identification

GHS product identifier : CIA-GEL 7000 PART B

Other means of identification

.

Product type :

Relevant identified uses of the substance or mixture and uses advised against

Identified uses :

Supplier's details :

Emergency telephone number (with hours of operation)

.

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

TOXIC TO REPRODUCTION (Fertility) - Category 1B TOXIC TO REPRODUCTION (Unborn child) - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) -

Category 1

AQUATIC HAZARD (ACUTE) - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 1

Carcinogenicity

: This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of this product will create a possible silica dust hazard).



Section 2. Hazards identification

GHS label elements

Hazard pictograms









Signal word

Hazard statements

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H350 - May cause cancer.

H360 - May damage fertility or the unborn child.

H372 - Causes damage to organs through prolonged or repeated exposure. (respiratory

tract)

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.

P273 - Avoid release to the environment.

P260 - Do not breathe dust.

P270 - Do not eat, drink or smoke when using this product.

P264 - Wash hands thoroughly after handling.

P272 (OSHA) - Contaminated work clothing must not be allowed out of the workplace.

Response

P391 - Collect spillage.

P314 - Get medical attention if you feel unwell.

P308 + P313 - IF exposed or concerned: Get medical attention.

P304 + P340 + P310 - IF INHALED: Remove person to fresh air and keep comfortable

for breathing. Immediately call a POISON CENTER or physician.

P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER

or physician. Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician.

P302 + P352 + P363 - IF ON SKIN: Wash with plenty of soap and water. Wash

contaminated clothing before reuse.

P333 + P313 - If skin irritation or rash occurs: Get medical attention.

P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage

: P405 - Store locked up.

Disposal

P501 - Dispose of contents and container in accordance with all local, regional, national

and international regulations.

Hazards not otherwise

: None known.

classified

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Other means of identification



Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Crystalline silica, respirable powder	≥50 - ≤75	14808-60-7
2-Piperazin-1-Ylethylamine	≥10 - ≤20	140-31-8
4-Nonylphenol, Branched	≥10 - ≤17	84852-15-3
Silica, amorphous, fumed, crystfree	≥1 - ≤1.1	112945-52-5
2-(2-Aminoethylamino)Ethanol	≥0.3 - <1	111-41-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes severe burns. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.





Section 4. First aid measures

Over-exposure signs/symptoms

Eye contact

: Adverse symptoms may include the following:

pain watering redness

Inhalation

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact

Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion

: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

: None known.

media

Specific hazards arising from the chemical

: This material is very toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide

carbon dioxide carbon monoxide nitrogen oxides metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.





Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Use respirator only if ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed. labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.





Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Crystalline silica, respirable powder	OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / (%SiO2+2) 8 hours. Form: Respirable NIOSH REL (United States, 10/2016). TWA: 0.05 mg/m³ 10 hours. Form: Respirable dust OSHA PEL (United States, 6/2016). TWA: 50 µg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 3/2017). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction
2-Piperazin-1-Ylethylamine 4-Nonylphenol, Branched Silica, amorphous, fumed, crystfree 2-(2-Aminoethylamino)Ethanol	None. None. NIOSH REL (United States, 10/2016). TWA: 6 mg/m³ 10 hours. None.

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, if required, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.



Section 9. Physical and chemical properties

Appearance

Physical state : Solid. Color Black. Odor Sliaht.

Density Not available. Odor threshold Not available. Hq : Not available. **Melting point** : Not available. Not available. **Boiling point** : Not applicable. Flash point **Evaporation rate** Not available. Flammability (solid, gas) : Not applicable. Lower and upper explosive : Not applicable.

(flammable) limits

Vapor pressure : Not available. Vapor density Not available. Specific gravity : Not available. **Solubility** : Not available. Partition coefficient: n-: Not available.

octanol/water

Auto-ignition temperature : Not available. **Decomposition temperature** : Not applicable. **Viscosity** : Not available. Flow time (ISO 2431) : Not available.

Volatile organic compounds : 0 g/L (tested per EPA CFR 40, Part 63, Subpart PPPP, Appendix A)

16 g/L (tested per EPA CFR 40, Part 60, method 24)

Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4-Nonylphenol, Branched Silica, amorphous, fumed, crystfree	LD50 Oral LD50 Oral LD50 Dermal	Rat	1300 mg/kg 3160 mg/kg	-
2-(2-Aminoethylamino)Ethanol	LD50 Dermai LD50 Oral		2250 mg/kg 3 g/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Piperazin-1-Ylethylamine	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
,	Skin - Severe irritant	Rabbit	-	24 hours 5 mg	-
4-Nonylphenol, Branched	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Severe irritant	Rabbit	-	24 hours 500 mg	-
2-(2-Aminoethylamino)Ethanol	Eyes - Severe irritant	Rabbit	-	50 mg	-
	Skin - Mild irritant	Rabbit	-	445 mg	-

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP
Crystalline silica, respirable powder Silica, amorphous, fumed, crystfree	-	1 3	Known to be a human carcinogen.

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Specific target organ toxicity (single exposure)

Name	Category	Target organs
Silica, amorphous, fumed, crystfree 2-(2-Aminoethylamino)Ethanol	0)	Respiratory tract irritation Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Target organs
Crystalline silica, respirable powder	Category 1	respiratory tract

Aspiration hazard

There is no data available.

Information on the likely routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes severe burns. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.





Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

: Adverse symptoms may include the following:

pain watering redness

Inhalation

: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact

: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion

Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: No known significant effects or critical hazards.

effects

Potential delayed effects

: No known significant effects or critical hazards.

Long term exposure

Potential immediate

effects

: No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General

: Causes damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity

: May cause cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity

: No known significant effects or critical hazards.

Teratogenicity

: May damage the unborn child.

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

: May damage fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	2221.9 mg/kg
Dermal	6486.4 mg/kg



Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
2-Piperazin-1-Ylethylamine 4-Nonylphenol, Branched	Acute LC50 2190000 μg/L Fresh water Acute EC50 0.03 mg/L Marine water Acute EC50 0.027 mg/L Marine water Acute EC50 137 μg/L Marine water	Fish - Pimephales promelas Algae - Skeletonema costatum Algae - Skeletonema costatum Crustaceans - Eohaustorius estuarius - Adult	96 hours 72 hours 96 hours 48 hours
	Acute LC50 17 μg/L Marine water Chronic EC10 0.012 mg/L Marine water Chronic NOEC 5 μg/L Fresh water Chronic NOEC 7.4 μg/L Fresh water	Fish - Pleuronectes americanus - Larvae Algae - Skeletonema costatum Crustaceans - Gammarus fossarum - Adult Fish - Pimephales promelas - Embryo	96 hours 96 hours 21 days 33 days

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Piperazin-1-Ylethylamine	-1.48	-	low
4-Nonylphenol, Branched	5.4	740	high
2-(2-Aminoethylamino)Ethanol	-1.46	<0.2	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Should be mixed with Part A. The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN3259	UN3259	UN3259
UN proper shipping name	AMINES, SOLID, CORROSIVE, N.O.S. (2-Piperazin-1-Ylethylamine, 4-Nonylphenol, Branched)	AMINES, SOLID, CORROSIVE, N.O.S. (2-Piperazin-1-Ylethylamine, 4-Nonylphenol, Branched). Marine pollutant (4-Nonylphenol, Branched)	AMINES, SOLID, CORROSIVE, N.O.S. (2-Piperazin-1-Ylethylamine, 4-Nonylphenol, Branched)



Section 14. Transport information

Transport hazard class(es)	8	8	8
Packing group	III	III	III
Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.

AERG: 154

Additional information

The limited quantity exception can be used for the transportation of this item. Certain restrictions may apply in regards to sizes and packaging. For further information, refer to the applicable transportation of dangerous goods regulation.

IMDG

: The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.

IATA

: The environmentally hazardous substance mark may appear if required by other

transportation regulations.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 final significant new use rules: 4-Nonylphenol, Branched

TSCA 8(a) PAIR: 4-Nonylphenol, Branched; Siloxanes and Silicones, di-Me, reaction

products with silica

TSCA 12(b) one-time export: 4-Nonylphenol, Branched

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

: Not listed

Class II Substances **DEA List I Chemicals**

(Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.





Section 15. Regulatory information

SARA 311/312

Classification

: SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 1A

TOXIC TO REPRODUCTION (Fertility) - Category 1B TOXIC TO REPRODUCTION (Unborn child) - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) -

Category 1

Composition/information on ingredients

Name	Classification
Crystalline silica, respirable powder	CARCINOGENICITY - Category 1A
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory
0.5:	tract) (inhalation) - Category 1
2-Piperazin-1-Ylethylamine	ACUTE TOXICITY (oral) - Category 4
	ACUTE TOXICITY (dermal) - Category 4
	SKIN CORROSION/IRRITATION - Category 1B
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1
4-Nonylphenol, Branched	ACUTE TOXICITY (oral) - Category 4
4-Nonyiphenoi, Branched	SKIN CORROSION/IRRITATION - Category 1B
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
	TOXIC TO REPRODUCTION (Fertility) - Category 2
	TOXIC TO REPRODUCTION (Unborn child) - Category 2
Silica, amorphous, fumed, crystfree	SKIN CORROSION/IRRITATION - Category 2
, , , , , , ,	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
	irritation) - Category 3
2-(2-Aminoethylamino)Ethanol	SKIN CORROSION/IRRITATION - Category 1B
	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
	SKIN SENSITIZATION - Category 1
	TOXIC TO REPRODUCTION (Fertility) - Category 1B
	TOXIC TO REPRODUCTION (Unborn child) - Category 1B
	SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract
	irritation) - Category 3

SARA 313

	Product name	CAS number
Form R - Reporting requirements	4-Nonylphenol, Branched	84852-15-3
Supplier notification	4-Nonylphenol, Branched	84852-15-3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

New York

Massachusetts : The following components are listed: Crystalline silica, respirable powder; 2-Piperazin-1-Ylethylamine

: None of the components are listed.

New Jersey : The following components are listed: Crystalline silica, respirable powder; 2-Piperazin-

1-Ylethylamine

Pennsylvania : The following components are listed: Crystalline silica, respirable powder; 2-Piperazin-1-Ylethylamine

California Prop. 65



WARNING: This product can expose you to chemicals including Crystalline silica, respirable powder, Titanium dioxide, which are known to the State of California to cause cancer, and Ethanediol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Section 15. Regulatory information

Ingredient name	No significant risk level	Maximum acceptable dosage level	
Ethanediol	-	Yes.	
Crystalline silica, respirable powder	-	-	l
Titanium dioxide	<u> </u>	-	

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION/IRRITATION - Category 1B	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION (Fertility) - Category 1B	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 1B	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (respiratory tract) -	Calculation method
Category 1	
AQUATIC HAZARD (ACUTE) - Category 1	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 1	Calculation method

History

Date of issue mm/dd/yyyy : 08/28/2018

Date of previous issue : Not applicable

Version : 1

Prepared by : KMK Regulatory Services Inc.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

