

# **PRODUCT SPECIFICATIONS**

## **OW-4 OMNIWALL SHINGLE OVER VENT**

### **1.1 MATERIALS:**

#### **1.1.1 Plastic Polymers:**

Custom blended, high impact co-polymer with UV stabilization additives.

#### **1.1.2 Aluminum Alloy:**

Screen: 18 mesh Aluminum screen.

### **1.2 MISCELLANEOUS:**

**1.2.1 Description:** Injection molded, shingle over vent for shed roof or up to wall applications. Molded in 4 foot sections. Adjustable to roof pitches from 3/12 to 16/12. Features an exterior venturi baffle with perpendicular omni baffles, internal aerodynamic curved baffles, molded end plugs, weather proof under lapping connection with alignment tabs, water shield at the louvers, fully supported nail holes, integrated flashing flap, and double row of internal aluminum screening for added weather protection. Molded nailing lines for cap shingles. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

**1.2.2 Color:** Available in BLACK.

**1.2.3 Net Free Area:** 9 square inches per linear foot. (36 square inches per 4 foot part.)

**1.2.4 Packaging:** Packaged 10 to a carton. Available in 4 foot lengths. UPC labels are affixed to each vent and carton.



P.O. Box 519  
Jacksonville, AR 72078  
1-800-643-5596 phone  
501-982-1258 fax