

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Version number 28

Preparation Date: 04.05.2017 Revision Date: 04.05.2017

Section 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- · Trade name:

FLX 1C-PU Construction adhesive

• Article number:

114900

Product Group

1-component polyurethan adhesive

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Product category

PC1 Adhesives, sealants

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

STAUF Klebstoffwerk GmbH Oberhausener Strasse 1 57234 Wilnsdorf, Germany

+49-(0)2739-301-0

+49-(0)2739-301-200

• 1.4 Emergency telephone number:

CARECHEM24- EU, +44 1235 239670

Section 2: Hazard(s) identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS08

Resp. Sens. 1 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 - H351 Suspected of causing cancer.

STOT RE 2 - H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 - H332 Harmful if inhaled.

Skin Irrit. 2 - H315 Causes skin irritation.

Eye Irrit. 2 - H319 Causes serious eye irritation.

Skin Sens. 1 - H317 May cause an allergic skin reaction.

STOT SE 3 - H335 May cause respiratory irritation.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008





GHS08 GHS07

 Signal word Danger

Section 2: Hazard(s) identification

· Hazard-determining components of labelling:

diphenylmethanediisocyanate,isomeres and homologues / 4,4'-methylenediphenyl diisocyanate / o-(p-isocyanatobenzyl)phenyl

isocyanate / 2,2'-methylenediphenyl diisocyanate

Hazard statements

H334 May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P284 [In case of inadequate ventilation] wear respiratory protection.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

Revision Date: 04.05.2017

lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P302+P352 IF ON SKIN: Wash with plenty of water.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT:

Not applicable.

vPvB:

Not applicable.

Section 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description:

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS Number		%
9016-87-9	diphenylmethanediisocyanate,isomeres and homologues	25,00- 50,00
	Carc. 2	
	♦ Resp. Sens. 1 - H334, Carc. 2 - H351,	
	STOT RE 2 - H373; 💠 Acute Tox. 4 - H332,	
	Skin Irrit. 2 - H315, Eye Irrit. 2 - H319,	
	Skin Sens. 1 - H317, STOT SE 3 - H335	
25322-69-4	Polypropyleneglycol	12,50- 25,00
	♠ Acute Tox. 4 - H302	
101-68-8	4,4'-methylenediphenyl diisocyanate	5,00- 12,50
	EC number: 202-966-0	
	Carc. 2	
	🕸 Resp. Sens. 1 - H334, Carc. 2 - H351,	
	STOT RE 2 - H373; 💠 Acute Tox. 4 - H332,	
	Skin Irrit. 2 - H315, Eye Irrit. 2 - H319,	
	Skin Sens. 1 - H317, STOT SE 3 - H335	
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	5,00- 12,50
	EC number: 227-534-9	
	Carc. 2	

Section 3: Composition/information on ingredients

Resp. Sens. 1 - H334, Carc. 2 - H351,

STOT RE 2 - H373; **1** Acute Tox. 4 - H332,

Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, Skin Sens. 1 - H317, STOT SE 3 - H335

2536-05-2 2,2'-methylenediphenyl diisocyanate 2,50- 5

EC number: 219-799-4

Carc. 2

Resp. Sens. 1 - H334, Carc. 2 - H351,

STOT RE 2 - H373; (1) Acute Tox. 4 - H332,

Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, Skin Sens. 1 - H317, STOT SE 3 - H335

96-48-0 gamma-butyrolactone 1,26- 2,50

EC number: 202-509-5

Acute Tox. 4 - H302, Eye Irrit. 2 -

H319

77-58-7 dibutyltin dilaurate 0.10- 0.25

EC number: 201-039-8

Skin Corr. 1B - H314; 🤏 Acute Tox.

3 - H301

Section 4: First-aid measures

4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

Rinse out mouth with water.

· Information for doctor:

4.2 Most important symptoms and effects, both acute and delayed

Headache

Coughing

Asthma attacks

Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

In cases of irritation to the lungs, initial treatment with Dexamethason metered aerosol.

Later observation for pneumonia and pulmonary oedema.

Section 5: Fire-fighting measures

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen, isocyanate vapors and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes.

• 5.3 Advice for firefighters

No special measures required.

· Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

Revision Date: 04.05.2017

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Section 7: Handling and storage

· Handling:

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

Avoid contact with eyes, skin and clothes.

· Information about fire - and explosion protection:

No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in dry conditions.

7.3 Specific end use(s)

No further relevant information available.

Section 8: Exposure controls/personal protection

 wor 	kpla	ace:
-------------------------	------	------

Ingredients w ith 9016-87-9 dip

ith limit values that require monitoring at the diphenylmethanediisocyanate, isomeres and

homologues

WEL

Short-term value Long-term value 0,07 0,02 mg/m3 mg/m3

Revision Date: 04.05.2017

Sen; as -NCO

101-68-8

4,4'-methylenediphenyl diisocyanate

WEL

Short-term value Long-term value 0.07 0.02 mg/m3 mg/m3

Sen; as -NCO

5873-54-1 WEL o-(p-isocyanatobenzyl)phenyl isocyanate

Short-term value Long-term value

0.07 0.02 mg/m3 mg/m3

Sen; as -NCO

2536-05-2

2,2'-methylenediphenyl diisocyanate

WEL

Short-term value Long-term value 0.07 0.02 mg/m3 mg/m3

Sen; as -NCO

Preparation Date: 04.05.2017 PRODUCT: FLX 1C-PU Construction adhesive Revision Date: 04.05.2017

Section 8: Exposure controls/personal protection

• DNELs

101-68-8 4,4'-methylenediphenyl diisocyanate
Inhalative, DNEL (dynamic): 0,05 mg/m3 (Workers)
5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate
Inhalative, DNEL (dynamic): 0,05 mg/m3 (Workers)

PNECs

101-68-8 4,4'-methylenediphenyl diisocyanate

PNEC: >0,1 mg/l PNEC: >1 mg/l

5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate

PNEC: >0,1 mg/l PNEC: >1 mg/l

Additional information:

The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work, use skin care products.

Keep away from foodstuffs, beverages and feed.

Do not inhale gases / fumes / aerosols.

- Respiratory protection: Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation.
- · Protection of hands: Protective gloves
- · Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye protection: Tightly sealed and solvent resistant goggles
- · Body protection: Protective work clothing

Section 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties				
General Information				
Appearance:				
Form:	Fluid			
Colour:	Yellowish			
Odour:	Characteristic			
Odour threshold:	Characteristic			
pH-value:	Not determined.			
Change in condition				
Boiling point/Boiling range:	Undetermined.			

Section 9: Physical and chemical properties

	, pg/
Flash point:	111 °C
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	400 °C
Decomposition temperature:	Not determined.
Self-igniting:	Not determined.
Danger of explosion:	Not determined.
Explosion limits:	
Lower:	0,40 Vol %
Upper:	Not determined.
Vapour pressure:	Not determined.
Density:	1,1400 g/cm3
Solubility in / Miscibility with	
water:	Not determined.
Viscosity:	
Dynamic:	at 20 °C 4.500 mPa.s
Solvent content:	
Organic solvents:	2,50 %
VOC (EC)	2,5000 %
9.2 Other information	No further relevant information available.

Section 10: Stability and reactivity

- 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Exothermic reaction with amines and alcohols; reacts with water forming CO2; in closed containers, risk of bursting owing to increase of pressure.

· 10.4 Conditions to avoid

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

· 10.6 Hazardous decomposition products:

Section 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values relevant for classification:

25322-69-4 Polypropyleneglycol

Oral, LD50: <2000 mg/kg (rat)

Dermal, LD50: >10000 mg/kg (Rabbit)

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral, LD50: >2000 mg/kg (rat) Oral, LD50: 2200 mg/kg (mouse) Dermal, LD50: >9400 mg/kg (Rabbit) Inhalative, LC50/4h: 0,368 mg/l (rat)

o-(p-isocyanatobenzyl)phenyl isocyanate

Oral, LD50: >2000 mg/kg (rat) Dermal, LD50: >9400 mg/kg (Rabbit) Inhalative, LC50/4h: 0,31 mg/l (rat) gamma-butyrolactone Oral, LD50: 1540 mg/kg (rat)

Dermal, LD50: 5000 mg/kg (guinea Pig) dibutyltin dilaurate 77-58-7

Oral, LD50: 175 mg/kg (rat)

Section 11: Toxicological information

- · Primary irritant effect:
- · on the skin:

Irritant to skin and mucous membranes.

on the eye:

Irritating effect.

· Sensitization:

Sensitisation possible through inhalation.

Sensitisation possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU

Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Carc. 2

Section 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity:

101-68-8 4,4'-methylenediphenyl diisocyanate

daphnie, NOEL/72h: >10 mg/l

· 12.2 Persistence and degradability

No further relevant information available.

- · Behaviour in environmental systems:
- 12.3 Bioaccumulative potential

No further relevant information available.

· 12.4 Mobility in soil

No further relevant information available.

- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT:

Not applicable.

vPvB:

Not applicable.

· 12.6 Other adverse effects

No further relevant information available.

Section 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08
WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF
COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS
AND PRINTING INKS
08 05
wastes not otherwise specified in 08
08 05 01
waste isocyanates

Revision Date: 04.05.2017

Section 14: Transport information

14.1 UN-Number
 ADR Void
 IMDG Void
 IATA Void

14.2 UN proper shipping name

ADR Void
IMDG Void
IATA Void

14.3 Transport hazard class(es)

ADR

Class Void
IMDG
Class Void
IATA

Class Void

14.4 Packing group

ADR Void
IMDG Void
IATA Void

• 14.5 Environmental hazards:

Not applicable.

 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

Section 15: Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

• REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3, 20, 56a, 56b, 56c

- · National regulations:
- · Technical instructions (air):

· Class Share in %

I 74,00 2.5 20,00

· Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

Section 16: Other information, including date of preparation or last version

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing MSDS:

Technical Department

· Contact:

Dr. Frank Gahlmann +49-(0)2739-301165 gahlmann@stauf.de

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

Revision Date: 04.05.2017

Preparation Date: 04.05.2017 PRODUCT: FLX 1C-PU Construction adhesive Revision Date: 04.05.2017

Section 16: Other information, including date of preparation or last version

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.