TAMKO® 10-INCH STARTER

STARTER COURSE SHINGLES

MANUFACTURED IN PHILLIPSBURG, KS



NOTICE: THIS PRODUCT IS SOLD "AS IS" AND WITHOUT WARRANTY OF ANY KIND. ALL WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED.

WARNING: USE OF POLYURETHANE FOAM INSULATION APPLIED DIRECTLY TO THE UNDERSIDE OF A ROOF DECK MAY CAUSE PREMATURE DEGRADATION OR FAILURE OF THIS ASPHALT ROOFING PRODUCT. WE ARE INVESTIGATING COMPATIBILITY OF POLYURETHANE FOAMS WITH OUR ASPHALT BUILDING PRODUCTS. CHEMICAL INCOMPATIBILITY, OFFGASSING AFTER APPLICATION AND EXCESS HEAT DURING AND AFTER APPLICATION OF POLYURETHANE FOAMS MAY AFFECT THE PERFORMANCE OF ASPHALT AND MODIFIED ASPHALT BUILDING PRODUCTS AND METAL FASTENERS USED WITH THOSE PRODUCTS.



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. The TAMKO Safety Data Sheet (SDS) is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost or debris will decrease the traction and can cause slippery conditions when walking on the product. Applicator safety is of utmost importance.

IN COLD WEATHER (BELOW 40°F), CARE MUST BE TAKEN TO AVOID DAMAGE TO THE EDGES AND CORNERS OF THE SHINGLES.

IMPORTANT: It is not necessary to remove the plastic strip from the back of the shingles.

CHECK LOCAL BUILDING CODES TO DETERMINE SUITABILITY OF THIS PRODUCT FOR YOUR INTENDED USE.

INFORMATION INCLUDED IN THESE APPLICATION INSTRUCTIONS WAS CURRENT AT THE TIME OF PRINTING. TO OBTAIN A COPY OF THE MOST CURRENT VERSION OF THESE APPLICATION INSTRUCTIONS, VISIT US ONLINE AT WWW.TAMKO.COM OR CALL US AT 1-800-641-4691.

TAMKO® 10-INCH STARTER

STARTER COURSE SHINGLES

MANUFACTURED IN PHILLIPSBURG, KS



Covers approximately 100 linear feet per bundle when installed according to TAMKO's Installation Instructions.

- Bundle contains 30 starter shingles
- Factory sealant strip
- Covers 100 linear feet per bundle when applied according to TAMKO's application Instructions.

The first course of shingles is the most critical to ensure proper alignment of the courses. TAMKO® 10-Inch Starter course shingles are factory cut to eliminate the difficulty of field cutting 3 tabs and roll roofing materials. The finished product helps to insure a straighter first course of shingles and reduces labor and waste.

TAMKO® 10-Inch Starter also comes with a factory sealant strip to eliminate the need for plastic cement. Start your next shingle project right-using 10-Inch Starter Course Shingles by TAMKO.

