

TAMKO® 12-1/4 x 12 HIP & RIDGE

ROOFING ACCESSORY

MANUFACTURED IN FREDERICK, MD

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.

12-1/4 x 12 HIP & RIDGE features a fiberglass mat coated on both sides with weathering-grade asphalt and surfaced with mineral granules. Covered by the TAMKO Limited Warranty and Arbitration Agreement for the TAMKO® shingles covering the field of the roof.

- Each shingle is perforated into 3 pieces for separation prior to application.
- Self-sealing strip of asphalt.

USES: Hip & Ridge forms a cap along various angles of the roof.

- For use with TAMKO® shingle products.

SHINGLES BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG SHINGLES WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

COLORS

- Aged Wood
- Antique Wood
- Autumn Brown
- Black Sage
- Black Walnut
- Cabin Wood Brown
- Cedar Wood
- Natural Timber
- Olde English Pewter
- Oxford Grey
- Rustic Black
- Rustic Cedar
- Rustic Evergreen
- Rustic Redwood
- Rustic Slate
- Slatetone Grey
- Thunderstorm Grey
- Virginia Slate
- Weathered Wood

TECHNICAL INFORMATION

UL Listed for Class A Fire Rating:	UL 790/ASTM E108, Class A
UL Classified for Wind Resistance:	ASTM D3161, Class F
UL Classified in accordance with:	ASTM D3462 and ICC-ES Acceptance Criteria AC438
UL Evaluation Reports:	UL ER2919-01 and UL ER2919-02
Florida Building Code Approved:	FL18355
Miami-Dade County Florida Approved:	NOA 14-1001.08 Expiration Date: 01/08/2019

PRODUCT DATA

Shingle sizes [†]	12-1/4" x 36"
Perforated Shingle size	12-1/4" x 12"
Exposure	5-1/8"
Perforated Shingles per 100 lineal feet	234
Bundles per 100 lineal feet	3

[†]Subject to manufacturing variation

WARNING: Use of polyurethane foam insulation applied directly to the underside of a roof deck may cause premature degradation or failure of this asphalt roofing product. We are investigating compatibility of polyurethane foams with our asphalt building products. Chemical incompatibility, off-gassing after application and excess heat during and after application of polyurethane foams may affect the performance of asphalt and modified asphalt building products and metal fasteners used with those products.



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. [The TAMKO Safety Data Sheet \(SDS\) is available at tamko.com/sds](http://tamko.com/sds). Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposure to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogen". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

TAMKO[®]
BUILDING PRODUCTS

P.O. Box 1404
Joplin, MO 64802-1404
800-641-4691
tamko.com