TAMKO[®] ASTM TILE

TILE UNDE	RLAYMENT Manufactured in Green Cove Springs, FL
	TAMKO® ASTM TILE UNDERLAYMENT features a tough TAMKO organic felt that is saturated with asphalt then coated on both sides with a weathering grade asphalt and surfaced with granules.
USES	Accepted for use as an underlayment felt to be applied over the deck prior to the installation of concrete tile.
ERTIFICATIONS	ASTM D 6380, CLASS M, TYPE II U.L. Prepared Roofing Accessory ASTM D 249, Type II
	Roll Dimensions 36' X 36"
	Coverage per roll 1 Square
	*All values stated as nominal
	THIS PRODUCT IS SOLD "AS IS" WITHOUT WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.
	Visit our Web Site at tamko.com
	CAUTION: This product contains crystalline silica and wood dust. Crystalline silica and wood dust have been classified as "known" human carcinogens by

to oxidized asphait and its emissions during rooming have been classified by UAPC as a proceable numan carcinogen. Uncluzed asphait also contains PolyCydic Aromatic Hydrocarbons some of which have been classified by IAPC as known or probable human carcinogens. The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or diffing during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.



TAMKO Logo, Roofer Logo and TAMKO® are registered trademarks of TAMKO® Building Products, Inc.

Central District Northeast District Southeast District Southwest District Western District

220 West 4th St. 4500 Tamko Dr. 2300 35th St. 7910 S. Central Exp. 5300 East 43rd Ave.

Joplin, MO	64801	800-641-4691
Frederick, MD	21701	800-368-2055
Tuscaloosa, AL	35401	800-228-2656
Dallas, TX	75216	800-443-1834
Denver, CO	80216	800-530-8868
Frederick, MD Tuscaloosa, AL Dallas, TX	21701 35401 75216	800-368-2055 800-228-2656 800-443-1834

PRODUCT DATA

Information included in this product data sheet was current at time of printing. To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800-641-4691.