



TECHNICAL NOTICE

February 8, 2019

USE OF A SINGLE LAYER OF MOISTURE GUARD® IN LIEU OF TWO LAYERS OF AN ACCEPTED SATURATED FELT FOR TAMKO® FIBERGLASS/ASPHALT SHINGLE LOW-SLOPE APPLICATION*

TAMKO accepts use of a single layer of Moisture Guard® in lieu of two-layers of an accepted saturated felt underlayment when installing TAMKO® fiberglass/asphalt shingles on pitches of two inches per foot to less than four inches per foot.

As stated in *Application Instructions for Moisture Guard Ice & Rain Underlayment* (Rev. 06/11/2018), when using Moisture Guard over the entire roof deck, “the roof must include a system to provide adequate ventilation for all space immediately below the roof deck. Such ventilation system should be designed in accordance with architectural design standards appropriate to the size, nature, and location of the structure and should include both ridge and soffit venting.”

This document is not intended nor should it be construed to modify or alter the terms of TAMKO’s *Fiberglass/Asphalt Shingle Limited Warranty and Arbitration Agreement* or *TAMKO TW Metal & Tile, TW Underlayment & Moisture Guard Limited Warranty and Arbitration Agreement*.

Additional information about TAMKO products is available at tamko.com.

* To obtain the current version of this Technical Notice, visit TAMKO’s website at tamko.com.

©2019 TAMKO Building Products, Inc. TAMKO, TAMKO logo, and Moisture Guard are registered trademarks of TAMKO Building Products, Inc.