

SBS MODIFIED BASE SHEET

MANUFACTURED IN JOPLIN. MO

PRODUCT DATA

DESCRIPTION

Information included in this product data sheet was current at time of printing.

To obtain a copy of the most current version of this product data sheet, visit us online at tamko.com or call us at 800–641–4691.

VERSA-BASE® consists of a TAMKO® fiberglass mat coated on both sides with SBS modified asphalt.

- May be applied by mopping with hot asphalt, mechanically fastening, or an approved cold adhesive.
- · Pliable, puncture and pull through resistant.
- · 5-year Limited Warranty and Arbitration Agreement.

USES: Base sheet applied by mopping in hot asphalt, by mechanically fastening or with approved cold adhesive.

LOW SLOPE AND COMMERCIAL PRODUCTS BEGIN TO AGE AS SOON AS THEY ARE EXPOSED TO NATURE. BUILDINGS EXPERIENCE AGING FACTORS DIFFERENTLY, SO IT IS DIFFICULT TO PREDICT HOW LONG LOW-SLOPE AND COMMERCIAL PRODUCTS WILL LAST. THAT'S WHY TAMKO PROVIDES A LIMITED WARRANTY, THAT INCLUDES A BINDING ARBITRATION CLAUSE AND OTHER TERMS AND CONDITIONS WHICH ARE INCORPORATED HEREIN BY REFERENCE. YOU MAY OBTAIN A COPY OF THE LIMITED WARRANTY AT TAMKO.COM OR BY CALLING 1-800-641-4691.

TECHNICAL INFORMATION

UL Classified Base Sheet/Ply Sheet for Roofing Systems

Independently tested for compliance with:	ASTM D6163, Type I
UL Evaluation Reports:	UL ER3225-01
Florida Building Code Approved	FL17491

Miami Dade County Product Control Approved

PRODUCT DATA

Reinforcement	Fiberglass Mat
Polymer Type	Styrene-Butadiene-Styrene (SBS)
Roll Size [†]	48' 2" × 39-3/8"
Roll Coverage††	1.5 Squares
	,

[†]Subject to manufacturing variation



IMPORTANT SAFETY INFORMATION: Do not install until all appropriate safety precautions have been read and understood. The TAMKO Safety Data Sheet (SDS) is available at tamko.com/sds. Always use appropriate fall protection equipment and wear appropriate personal protective equipment (PPE) when working with this product. Moisture, frost, debris or other material will decrease the traction and can cause slippery conditions when walking on the product. **Applicator safety is of utmost importance.**

WARNING: This product contains crystalline silica and formaldehyde. Crystalline silica and formaldehyde have been classified as "known human carcinogens" by the International Agency for Research on Cancer (IARC) and the National Toxicology Program. This product also contains oxidized asphalt. Occupational exposures to oxidized asphalt and its emissions during roofing have been classified by IARC as a "probable human carcinogen". Oxidized asphalt also contains Polycyclic Aromatic Hydrocarbons some of which have been classified by IARC as "known" or "probable human carcinogens". The physical nature of this product may help limit any inhalation or dermal hazard during application and/or removal. However, physical forces such as sawing, grinding or drilling during demolition work and heating or burning may increase the inhalation or dermal exposure hazard of this product. Take precautions to prevent breathing and contact with skin.

WARNING: Use of this product in "hot mopped" applications may expose workers and others in the work area to oxidized asphalt and its emissions. The International Agency for Research on Cancer has classified occupational exposures to oxidized asphalt and its emissions during roofing as a "probable human carcinogen". During installation and removal of this product, including "hot mopped" application, workers must take precautions to assure adequate ventilation and use effective personal protective equipment to prevent exposures to dusts, fumes, vapors and mists. It is the responsibility of the contractor and workers to protect themselves and others in the work area from exposure to oxidized asphalt and its emissions when applying this product.



P.O. Box 1404 Joplin, MO 64802-1404 800-641-4691 tamko.com

^{††}When applied according to application instructions