

"The Professional's Choice"™

MATERIAL SAFETY DATA SHEET

Date of issue: April 21, 2010

1. Product and company identification

Product name: Grabber Wet n Stick® Water-Activated Joint Tape (W85)

CAS Number: None

HMC Tariff Code: 4823.12.0000

FSC: 8030

Technical Review Date: August 5, 2009 ASTM C-475, VT #100-3286-2,

November 3, 2009 ASTM C-474, VT #100-3355-2

Supplier: Grabber Construction Products

205 Mason Circle Concord, CA 94520

Emergency telepone: (412) 434-4515 (U.S.) number (514) 645-1320 (Canada)

01-800-00-21-400 (Mexico)

Technical phone number 800-877-TURN (Concord, California) 8:00 a.m. - 5:00 p.m PST

Product Class: Interior Wall Assembly
Product Use: Gypsum Panel Joint Tape

SIC Product Code: 2679

HMC Tariff/Product Code: 4823.12.0000

Division: Drywall Construction Material

2. Hazards identification

NFPA (USA)	WHMIS (Canada)	Transport Symbol	
000	Not Controlled	Not Regulated for Transportation	

Health Hazards Acute & Chronic:

ACUTE/CHRONIC: NONE KNOWN.

TARGET ORGANS: LUNGS.

Signs & Symptoms of

Overexposure: NONE SPECIFIED BY MANUFACTURER.

Medical Conditions

Aggravated by Exposure: NONE KNOWN

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.

Route of Entry Indicators:

Inhalation: YES

Skin: NO Ingestion: NO

Carcinogenicity Indicators NON-TOXIC

NTP: NO IARC: NO OSHA: NO

Carcinogenicity Explanation: NOT RELEVANT

Page: 1/4

MATERIAL SAFETY DATA SHEET

Date of issue: January 1, 2010

3. Composition/Information on Ingredients

Ingredient Name: CELLULOSE; (CELLULOSE FIBER), 85-90 lb. KRAFT PAPER Natural or Bleached

Water-Activated GUM: Corn Starch based, water-soluble coating –Ingredients (PROPRIATARY)

Ingredient:

CAS Number: 9004-34-6

CAS Code: M Code: % Low Volume: %Low

Text: 90-100 % Environmental Weight: Other REC Limits: N/KOSHA PEL: 15 MG/M3 TDUST

OSHA PEL Code: M OSHA STEL: OSHA STEL Code: ACGIH TLV: 10 MG/M3 ACGIH TLV Code: M ACGIH STEL: N/P ACGIH STEL Code: EPA Reporting Quantity: DOT Reporting Quantity: Ozone

Depleting

Chemical:

Ingredient Name: SIZING (NOT UREA FORMALDEHYDE)

Ingredient CAS Number: Ingredient CAS

Code: XRTECS
Number: RTECS
Code: X

4. First Aid Measures

First Aid:

Ingest: Call MD immediately (fp n).

Inhale: Remove to fresh air. Support breathing (give o*2/artf resp) (fpn).

Eyes: Immediately flush w/potable water for a minimum of 15 minutes; seek assistance from MD (fp n).

Skin: If cut by paper edge of tape, treat as any paper cut.

5. First Fighting Measures

USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire or

Explosion Hazard: NONE

Extinguishing Media: WATER, CO2, FOAM, and DRY CHEMICALS

Flash Point:

Flash Point Text:

Auto ignition Temperature:

Solubility:

Lower Limit(s):

Upper Limit(s):

NONE

230°C

negligible

N/K

N/K

6. Accidental Release Measures

Spill Release Procedures: PICK UP

7. Handling and Storage

Handling and Storage

Precautions: N/A
Other Precautions: N/A

Page: 2/4

MATERIAL SAFETY DATA SHEET

Date of issue: January 1, 2010

8. Exposure Controls and Personal Protection

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN (FP N).

Ventilation: NONE SPECIFIED BY MANUFACTURER.

Protective Gloves: IMPERVIOUS GLOVES (FP N).

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: NONE SPECIFIED BY MANUFACTURER. Work Hygienic Practices: NONE SPECIFIED BY MANUFACTURER.

Supplemental Health &

Safety Information: NONE SPECIFIED BY MANUFACTURER.

9. Physical and Chemical Properties

Tensile Strength:

Specimen#	Length (in)	Thickness (in)	Width (in)	Force (lbs)	lbf/in
1	2.063	0.009	0.997	31.0	31.1
2	2.063	0.009	1.003	32.1	32.0
3	2.063	0.009	0.998	37.7	37.8
4	2.063	0.009	1.003	32.6	32.5
5	2.063	0.009	0.989	32.2	32.6
6	2.063	0.009	0.973	35.8	36.8
7	2.063	0.009	0.990	28.8	29.1
8	2.063	0.009	0.990	34.6	34.9
9	2.063	0.009	0.987	34.6	35.1
<u>10</u>	<u>2.063</u>	0.009	1.010	<u>36.2</u>	<u>35.8</u>
Average:	2.063	0.009	0.994	33.6	33.8

Dimensional Stability:

Specimen#	Dry	Length Wet	% Expansion	Dry	Width Wet %	Expansion
1	9.344	9.344	0.000	2.063	2.063	0.000
2	9.219	9.219	0.000	2.063	2.063	0.000
3	9.344	9.344	0.000	2.063	2.063	0.000
Average:			0.000			0.000

Boiling Point:

Boiling Point Text: N/K

Melting/Freezing Point:

Melting/Freezing Text: N/K

Decomposition Point:

Decomposition Text: N/K
Vapor Pressure: N/K
Vapor Density: N/K

Percent Volatile Organic Content:

Specific Gravity: <1 (H*2O=1)

Volatile Organic Content Pounds per Gallon:

pH: N/K

Volatile Organic Content Grams per Liter:

Viscosity: N/P
Evaporation Weight and Reference: N/K

Solubility in Water: PAPER-INSOLUBLE; APPLIED COATING- WATER SOLUABLE Appearance and Odor: KRAFT MANILA PAPER 2" – 6"WIDE, Natural or White

Percent Volatiles by Volume: N/K
Corrosion Rate: N/K

sion Rate: N/K Page: 3/4

MATERIAL SAFETY DATA SHEET

Date of issue: January 1, 2010

SDS#: 15-01

10. Stability and Reactivity

Materials to Avoid:

Stability Indicator: YES, GUMMED ADHESIVE ACTIVATES UPON CONTACT WITH WATER

NONE SPECIFIED BY MANUFACTURER.

Stability (Condition to Avoid): Stable HIGH TEMPERATURES.

Hazardous Decomposition Products: CO, CO*2.
Hazardous Polymerization Indicator: Will not occur
Conditions to Avoid Polymerization: NOT RELEVANT

11. Toxicological Information

Toxicological Information: NON-TOXIC, ODORLESS, STARCH BASED, WATER SOLUABLE, GUMMED ADHESIVE

12. Ecological Information

Non-toxic - contains mold preventive gummed adhesive that is a water-activated; 100% biodegradable, eliminates significant compound waste; no energy requirement. The paper is from the Sustainable Forest Initiative (SFI); Chain-of-Custody (CoC) certified – FSC CoC controlled wood standard.

13. Disposal Considerations

Waste Disposal Methods: DISPOSAL MUST BE I/A/W FEDERAL, STATE & LOCAL REGULATIONS (FP N). TO SANITARY LANDFILL

14. Transport Information

Transport Information: NON-HAZARD

15. Regulatory Information

SARA Title III Information: N/P
Federal Regulatory Information: N/P
State Regulatory Information: N/P

16. Other Information

Label Required Indicator: N Status Code: C

Manufacturer's Label Number: WNS250

Organization Code:
Chronic Hazard Indicator:
Health Hazard:
Contact Hazard:
None
Fire Hazard:
None
Reactivity Hazard:
None

Disclaimer: The compilation of information in this document is information derived by the product

material sources of Dura-Tape International. While the information and recommendations set forth herein are believed to be accurate, Dura-Tape International, their suppliers and their distributors make no warranty with respect thereto and disclaim all liability from reliance

thereon.